Medium Duty Truck ZERO EMISSIONS

The fully electric commercial EVI-MD is versatile, flexible, and loaded with environmental benefits. The EVI-MD supports a wide range of bodies and chassis-mounted equipment for various vocations. Gross Vehicle Weight's range from class 5 to class 6 with top speeds of 65 miles per hour. The EVI-MD is extremely agile with up to a 55-degree wheel cut for excellent maneuverability.

The EVI-MD is the right choice for your fleet, the environment, and the future.



Applications

EVI-MD applications include:

Dry Freight Delivery Refrigerated Freight Beverage

Utility

Construction Landscaping

Ground Support

Specifications

EY SPECIFICATIONS	
Maximum Speed	65 mph*
Average Range	90 Miles*
Acceleration (0-60 mph)	26 Seconds at 19,500 lb.
GVWR	Class 5 (16,001 lb.) — Class 6 (23,000 lb.)
Wheel Base	155"— 270"
ATTERY SYSTEM	
Make	Valence Technology
Chemistry	Lithium Iron Magnesium Phosphate (LiFeMgP04)
Туре	U-Charge XP®
Energy	99 kWh
Warrantied Battery Life	1,500 Cycles or 5 Years
OTOR	
Туре	AC Permanent Magnet
Continuous Rated Power	120 kW
Peak Rated Power	200 kW/260 hp
Maximum Torque	900 Nm/664 lbf.ft
RANSMISSION	
Description	2 Speed Automatic Manual
HARGER	
Charging Time	Scalable 6 — 12 Hours (J1772 Compliant)

*May vary based on GVWR, applications, driver habits, and road conditions.

(6 Hours: 220 Vac/75 amp)